10-2-00

-Please type a plus sign (+) inside this box [+]

ype a plus sign (+) inside this box [+]

Approved for use through 09/30/00. OMB 0651-0032

Patent and Trademark Office: U.S. DEPARTMENT OF COMMERCE

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number.



UTILITY PATENT APPLICATION TRANSMITTAL

(Only for new nonprovisional applications under 37 CFR 1.53(b)

Attorney Docket No. 003551.P007	Total Pages 3
First Named Inventor or Application Identifier Thomas W. Jewitt	
Express Mail Label NoEL 234 217 497 US	
ADDRESS TO: Assistant Commissioner for Patents Box Patent Application	

	wasnington, D. C. 20231										
		ELEMENTS									
See	See MPEP chapter 600 concerning utility patent application contents.										
1.											
2.	<u>X</u>	Specification (Total Pages <u>25</u>) (preferred arrangement set forth below) - Descriptive Title of the Invention - Cross References to Related Applications - Statement Regarding Fed sponsored R & D - Reference to Microfiche Appendix - Background of the Invention - Brief Summary of the Invention - Brief Description of the Drawings (if filed) - Detailed Description - Claims - Abstract of the Disclosure									
3.	_X_	Drawings(s) (35 USC 113) (Total Sheets 13)									
4.	<u>X</u>	Oath or Declaration (Total Pages 4_)									
		a. X Newly Executed (Original or Copy)									
		b Copy from a Prior Application (37 CFR 1.63(d)) (for Continuation/Divisional with Box 17 completed) (Note Box 5 below)									
		i <u>DELETIONS OF INVENTOR(S)</u> Signed statement attached deleting inventor(s) named in the prior application, see 37 CFR 1.63(d)(2) and 1.33(b).									
5.		Incorporation By Reference (useable if Box 4b is checked) The entire disclosure of the prior application, from which a copy of the oath or declaration is supplied under Box 4b, is considered as being part of the disclosure of the accompanying application and is hereby incorporated by reference therein.									
6.		Microfiche Computer Program (Appendix)									

7.	/II	Nucleotide and/or Amino Acid Sequence Submission
	(if applica a.	ble, all necessary) Computer Readable Copy
	b c	Paper Copy (identical to computer copy) Statement verifying identity of above copies
		ACCOMPANYING APPLICATION PARTS
8.	_X	Assignment Papers (cover sheet & documents(s))
9.		a. 37 CFR 3.73(b) Statement (where there is an assignee)
	X_	b. Power of Attorney (Executed)
10.		English Translation Document (if applicable)
11.		a. Information Disclosure Statement (IDS)/PTO-1449
		b. Copies of IDS Citations
12.		Preliminary Amendment
13.	_X	Return Receipt Postcard (MPEP 503) (Should be specifically itemized)
14.		a. Small Entity Statement(s)
		b. Statement filed in prior application, Status still proper and desired
15.		Certified Copy of Priority Document(s) (if foreign priority is claimed)
16.	X	Other: Attorney signature page including Copy of postcard and Certificate of Express
10.		Mailing pursuant to CFR §1.10.
17.	If a COI	NTINUING APPLICATION, check appropriate box and supply the requisite information:
	c	ontinuation Divisional Continuation-in-part (CIP)
		of prior application No:
18.	Corre	espondence Address
ļ	Custo	omer Number or Bar Code Label (Insert Customer No. or Attach Bar Code Label here)
		or
_X	_ Corre	spondence Address Below
NAM	1E <u>Denn</u>	nis A. Nicholls, Reg. No. 42,036
	BL	AKELY, SOKOLOFF, TAYLOR & ZAFMAN LLP
ADE	DESS	12400 Wilshire Boulevard
,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,		
		Seventh Floor
CITY	Los An	geles STATE California ZIP CODE 90025-1026
Cou	ntrv II	LS.A. TELEPHONE (408) 720-8598 FAX (408) 720-9397

-2-

BLAKELY, SOKOLOFF, TAYLOR & ZAFMAN LLP

Date: 28 Last., 2000 By Janu	a Kulis
	S A. Nicholis
	Io. 42,036
12400 Wilshire Blvd.	10. 42,000
Seventh Floor	
Los Angeles, CA 90025-1026	
(408) 720-8300	
(, . =	
EXPRESS MA	AIL CERTIFICATE OF MAILING
"Express Mail" mailing label number: EL 234	217 497 US
Date of Deposit: September	28, 2000
I hereby certify that I am causing this paper	or fee to be deposited with the United States Postal Service
	vice on the date indicated above and that this paper or fee
	issioner for Patents, Washington, D.C. 20231
Tina Domin	
(Typed or printed name of person mailing pa	
(Typed of printed name of person realing pa	the or ree)
Moring	
(Signature of person mailing paper or fee)	
f.	28-2110
	-0 8000
(Date signed)	
	s ·
Serial/Patent No.: * *	Filing/Issue Date: Herewith
Client: Oak Technology, Inc.	obust De-Screening Filter
Title: System and Method For A R	obust De-Screening Filter
BSTZ File No.: 03551.P007-	Atty/Secty Initials: JAS/DAN/td
Date Mailed: 9-28-2000	Docket Due Date: * *
The following has been received in the U.S. Pa	tent & Trademark Office on the date stamped hereon:
Amendment/Response (pgs.)	XXX Express Mail No.: EL234217497US
Appeal Brief (pgs.) (in triplicate)	Month(s) Extension of Time Amt: \$1.000.00
Application - Utility (25 pgs., with cover and abstract)	Information Disclosure Statement & PTO 1449 (pgs.) Check No
Application - Rule 1.53(b) Continuation (pgs.)	☐ Issue Fee Transmittal Amt:
Application - Rule 1.53(b) Divisional (pgs.)	□ Notice of Appeal
Application - Rule 1.53(b) CIP (pgs.)	Petition for Extension of Time
Application - Rule 1.53(d) CPA Transmittal (pgs.)	Petition for
Application - Design (pgs.)	Postcard
Application - PCT (pgs.)	Power of Attorney (pgs.)
Application - Provisional (pgs.)	Preliminary Amendment (pgs.)
Assignment and Cover Sheet	Reply Brief (pgs.)
Certificate of Mailing (Express Mail)	Response to Notice of Missing Parts
XX Declaration & POA (4 pgs.) (Executed)	Small Entity Declaration for Indep. Inventor/Small Business Transmittal Letter, in duplicate (3 pages)
Disclosue Doss & Oig & Copy of Inventor's Signed Leter (pg) Drawings: 13 # of sheets includes 14 figures	Transmittal Letter, in duplicate (5 pages) Fee Transmittal, in duplicate
→ Drawings: → → # or sneets includes → □ ngures	100 Transmittan, in turpricate
☐ Other:	
_ out.	

	Side	apsiw		FEE TRANSMITTAL FOR FY			a law one some manual.
				TOTAL AMOUNT OF PAYMENT (\$)	\$ 1	,000.00	
Appli Filing First I Group Exam	olete if Kn cation No Date Named In Art Unit iner Name	. <u>No</u> <u>Se</u> ventor <u>TI</u> <u>No</u>		28, 2000 (concurrently herewith /. Jewitt ssigned ssigned			
METI	HOD OF	PAYMEI	VT (che	ck one)			
1.	[X] Th		issione er paym	is hereby authorized to charge indicated to:	ted fees	and credit	
				nt Number <u>02-2666</u> nt Name			
	[] Ch	arge An	y Additi	onal Fee Required Under 37 CFR 1.16	and 1.17	7	
2.	<u>X</u>	Payme X	nt Enclo — — —	osed: Check Money Order Other			
FEE (CALCUL	ATION					
1.	BASIC F		EE				
	Entity	Small I					
Fee Code 101 106 107 108 114	Fee (\$) 690 310 480 690	Fee Code 201 206 207 208 214	Fee (\$) 345 155 240 345 75	Fee Description Utility application filing fee Design application filing fee Plant filing fee Reissue filing fee Provisional application filing fee			Fee Paid 690.00
					SUBT	OTAL (1) \$ <u>6</u>	90.00
2.	EXTRA	CLAIM F	EES	Extra Claims		Fee from below	Fee Paid
	Claims endent (22 Claims	6	-20** = <u>2</u> -3** = 3	X X	<u>18.00</u> = 78.00 =	36.00 234.00
Multi	ple Depe	ndent				=	
				, if greater; For Reissues, see belov	w.		
	Entity	<u>Small I</u> Fee	<u>Entity</u> Fee				
Fee Code	Fee (\$)	ree Code	ree (\$)	Fee Description			
103	18	203	9	Claims in excess of 20			
102	78	202	39	Independent claims in excess of 3			
104	260	204	130	Multiple dependent claim, if not paid			
109 110	78 18	209 210	39 9	**Reissue independent claims over or **Reissue claims in excess of 20 and			
110	10	2 I V	J	neissuc Ciainis III EACESS OI 20 ANG		BTOTAL (2)	270.00

FEE CALCULATION (continued) 3. **ADDITIONAL FEES** Large Entity **Small Entity** Fee Fee Fee Fee Code Code (\$) (\$) **Fee Description** Fee Paid 105 130 205 65 Surcharge - late filing fee or oath 127 50 227 25 Surcharge - late provisional filing fee or cover sheet 139 130 139 130 Non-English specification 147 2.520 147 2.520 For filing a request for reexamination 112 920* 920* Requesting publication of SIR prior to 112 **Examiner action** 113 1.840* 113 1.840* Requesting publication of SIR after **Examiner action** 115 110 215 55 Extension for response within first month 116 380 216 190 Extension for response within second month 870 117 217 435 Extension for response within third month 118 1,360 680 218 Extension for response within fourth month 128 1,850 228 925 Extension for response within fifth month 119 300 219 150 **Notice of Appeal** 120 300 150 Filing a brief in support of an appeal 220 121 260 221 130 Request for oral hearing 138 1,510 138 1,510 Petition to institute a public use proceeding 140 110 55 240 Petition to revive unavoidably abandoned application 141 1,210 241 605 Petition to revive unintentionally abandoned application 605 142 1,210 242 Utility issue fee (or reissue) 143 430 243 215 Design issue fee 144 580 244 290 Plant issue fee 122 130 122 130 **Petitions to the Commissioner** 123 50 123 50 Petitions related to provisional applications 126 240 126 240 **Submission of Information Disclosure Stmt** 581 40 581 40 Recording each patent assignment per property (times number of properties) 40.00 146 690 246 345 For filing a submission after final rejection (see 37 CFR 1.129(a)) 149 690 249 345 For each additional invention to be examined (see 37 CFR 1.129(a)) Other fee (specify) Other fee (specify) SUBTOTAL (3) \$ 40.00 *Reduced by Basic Filing Fee Paid SUBMITTED BY: Typed or Printed Name: Date Signature 42,036 Reg. Numbér/ **Deposit Account User ID** (complete if applicable)

UNITED STATES PATENT APPLICATION

FOR

SYSTEM AND METHOD FOR A ROBUST DE-SCREENING FILTER

INVENTOR:

THOMAS W. JEWITT

PREPARED BY:

BLAKELY, SOKOLOFF, TAYLOR & ZAFMAN LLP 12400 WILSHIRE BOULEVARD SEVENTH FLOOR LOS ANGELES, CA 90025-1026

(408) 720-8300

ATTORNEY'S DOCKET NO. 003551.P007

EXPRESS MAIL CERTIFICATE OF MAILING

"Express Mail" mailing label number <u>EL 234 217 497 US</u>

Date of Deposit <u>September 28, 2000</u>

I hereby certify that I am causing this paper or fee to be deposited with the United States Postal Service "Express Mail Post Office to Addressee" service under 37 CFR 1.10 on the date indicated above and is addressed to the Commissioner of Patents and Trademarks, Washington, D.C. 20231

Tina Domingo
(Typed or printed name of person mailing paper or fee)

| June | J-27-2000 |
(Signature of person mailing paper or fee) Date

10

15

20

SYSTEM AND METHOD FOR A ROBUST DE-SCREENING FILTER

FIELD OF THE INVENTION

The present invention relates to halftone printing technology, and more specifically, to undoing the effects of halftone printing technology.

BACKGROUND

Photographic images may be printed onto photographic film with great ease. All that is required is an optical path and unexposed film. In contrast with this, printing onto with a finite number of inks or wax transfers requires a technique that allows for gradation of shades with a single ink color. Each ink gives only the possibility of being applied (full intensity) or not being applied (zero intensity).

Perhaps the most common technique for allowing gradation of shades is the halftone system. In the halftone system, to emulate a gray midway between black and white, a small number of dots is printed on a white background. The ratio of the area covered by the dots to the area left uncovered determines how gray is the area.

Referring now to Figure 1, a diagram of a photographic film based halftone system is shown. Other halftone systems may utilize digital techniques, but the outcome is approximately the same. In the Figure 1 example, an original print 100 has medium gray area 102, light gray

10

15

20

area 106, dark gray area 104, white area 110, and black area 108. The original print 100 is projected via lens 120 onto a contact screen 124 and finally onto a film negative 142. The contact screen is a precision piece of film with a pattern of transparent areas 126 alternating in a grid with opaque areas 128. The contact screen is so constructed that the opacity gradually changes from total in opaque areas 128 to not opaque in transparent areas 126.

In a controlled exposure, light coming from a white area 110 is intense enough that the entire area 138 is exposed (blackened on a negative). But with no light coming from a black area 108 the area 140 is not exposed at all (stays white on a negative). In a medium gray area 102, the reflected light is strong enough to expose the film negative 136 in much of the area adjacent to the corresponding transparent areas of contact screen 124 but not strong enough to expose the film negative 142 in the area adjacent to the corresponding opaque areas of contact screen 124. This yields an area of medium-sized dots 132. For the light gray area 106 the exposure yields an area of larger dots 134, and for the dark gray area 104 the exposure yields an area of smaller dots 136.

The film negative 142 may be used as a printing master, with the black areas etched so that only the white areas can carry the ink.

When viewed from a suitable distance, an image printed from film

10

15

20

negative 142 has a corresponding replica of the original print 100. When viewed from a suitable distance, the replica will look like the original print 100 to a viewer.

The Figure 1 discussion was concerned with traditional optics and photographic film. A similar process may be performed with digital technology, wherein the contact screen is replaced by a digital sampling technique. The resulting dotted image may be used to generate a printing master in an analogous manner.

Referring now to Figure 2, a diagram showing screen angles in a color halftone system is shown. The Figure 1 discussion was for a black and white image. When printing color images, additional complications arise. Printing in color requires the use of the three subtractive primary colors, cyan (C), magenta (M), and yellow (Y). To achieve the best results, a fourth ink, black (K) is added to the CMY palate, creating a CMYK palate.

Four separate exposures, under different colored lights, create four separate film negatives for use as printing masters. However, printing inks are somewhat opaque, and if the same orientation of the contact screen is used for each color, what you will see is a print with the dots stacked one on top of the other. The dot printed last would be most visible. Therefore, the contact screen is rotated by an angle prior to the exposures that create the C film negative, the M film negative, the

10

15

20

Y film negative, and the K film negative. The best results occur when there is a 30 degree angle between the exposures. However, with four colors this is not possible. A best compromise has been found where the C, M, and K exposures are made with the contact screen rotated by 30 degrees between exposures, and by making the Y exposure with the contact screen midway between the C and M angles. One such possibility is shown in Figure 2. When the corresponding film negatives are converted into printing masters, a four-color CMYK halftone print may be printed.

Problems arise when the resulting CMYK halftone print is itself a candidate for subsequent scanning. When the resulting scanned image is used for either printing or direct electronic use, such as posting the image on a web page, the halftone nature of the source image will cause poor quality in either of the resulting images. Such subsequent scanning and printing or other use may take place in a computer system with a scanner and laser printer, or may take place in a digital photocopier. In each case complications arise because the CMYK halftone print has already gone through the halftone process. After scanning, subsequent attempts with screening processes may produce a poor subsequent halftone print, with blurry areas and the possibility of Moire effects. These effects are well-known to anyone who has attempted to make a photocopy of a halftone print. Similarly, after

10

15

scanning, subsequent use as an electronic image on a web page will exhibit poor image quality.

Prior art techniques for avoiding these problems have been limited by a requirement of either knowing detailed information about how the source halftone print was produced, or by using an inefficient trial-and-error method. The detailed information required may include the screen frequency (inversely proportional to the distance between transparent areas in a contact screen), screen angles (such as shown in Figure 2), the shape of the halftone dots, and many other parameters. It is highly unlikely that a copy machine operator would know the values of these parameters or even what they are. There are currently about 20 halftone screening procedures in common use, and each requires a specific procedure to undo the effects of the halftone screening. The large number of these procedures may make their use on a trial-and-error basis very time consuming.

10

SUMMARY OF THE INVENTION

A method and apparatus for de-screening a halftone image, therefore allowing the recovery of an approximation of an original image, is disclosed. A method according to one embodiment first performs a screen conversion filter upon a scanned representation of the halftone image to produce an intermediate image. This method then performs a line smoothing filter upon the intermediate image to produce an output image that approximates an original image.

In an alternate embodiment, the method performs a single convolution filter upon a scanned representation of the halftone image to produce an output image. In this embodiment, the single convolution filter is equal to the resulting convolution of first performing a screen conversion filter and then performing a line smoothing filter.

10

15

20

BRIEF DESCRIPTION OF THE DRAWINGS

The present invention is illustrated by way of example, and not by way of limitation, in the figures of the accompanying drawings and in which like reference numerals refer to similar elements and in which:

Figure 1 is a diagram of a photographic film based halftone system.

Figure 2 is a diagram showing screen angles in a color halftone system.

Figure 3 is an illustration of one embodiment of a computer system.

Figure 4 is a block diagram of one embodiment of a computer system in accordance with the present invention.

Figure 5 is a software module diagram of one embodiment of the computer system in accordance with the present invention.

Figure 6 is a chart illustrating the calculation of a filtered value for a pixel, according to one embodiment of the present invention.

Figure 7A is a diagram of a first convolution filter according to one embodiment of the present invention.

Figure 7B is a diagram of a second convolution filter according to one embodiment of the present invention.

Figure 8 is a diagram of a scanned image of one embodiment of the present invention.

10

Figure 9 is a diagram of an output image from a first filter according to one embodiment of the present invention.

Figure 10 is a diagram of an output image from a second filter according to one embodiment of the present invention.

Figure 11 is a graph of a first convolution filter frequency response according to one embodiment of the present invention.

Figure 12 is a graph of a second convolution filter frequency response according to one embodiment of the present invention.

Figure 13 is a graph of a combined filter frequency response according to another embodiment of the present invention.

10

15

20

DETAILED DESCRIPTION

A system and method for recreating a source image from an existing ("parent") halftone print is described. This method will be referred to as a "de-screening" process, because it aims to undo the effects created in a prior operation by a halftone contact screen or its digital equivalent. A system using this method will be referred to as a "de-screening filter". In the de-screening process, detailed knowledge of the prior halftone process is not necessary to create a subsequent ("daughter") halftone print in a laser printer or photocopier.

The de-screening process begins with the scanning of the parent halftone print. The digital representation created by this scanning process is then processed by a screen conversion filter. The output of the screen conversion filter is then processed by a line smoothing filter. The output of the line smoothing filter is a digital representation which may serve as the digital representation of the original parent image. This digital representation of the original parent image may then be processed in a subsequent halftone process to produce a clear daughter halftone print.

Referring now to Figure 3, an illustration of one embodiment of a computer system 300 of the present invention is shown. The computer system 300 includes a computer 310, a scanner 314, a laser printer 318, a monitor 322, and a keyboard 326. The component of the

10

15

20

computer system 300 are connected via scanner interface cable 312, printer interface cable 316, monitor interface cable 320, and keyboard interface cable 324. A parent halftone print 350 may be inserted into scanner 314 for the purpose of scanning. The laser printer 318 may then produce a subsequent daughter halftone print 360. In other embodiments, the components of computer system 300 or their equivalents may be combined into a digital photocopier.

Scanner 314 may be used to produce a digital representation of the parent halftone print 350 under control of computer 310. An operator using keyboard 326 and monitor 322 may select portions of the scanned digital representation for subsequent processing and printing on laser printer 318. Computer 310 may coordinate these efforts, and, additionally, may perform the screen conversion filter and line smoothing filter operations of the present invention. In alternate embodiments, these filtering operations may be performed by embedded processors within laser printer 318 or scanner 314.

Referring now to Figure 4, a block diagram of one embodiment of a computer system is shown, in accordance with the present invention. Computer 310 may include a central processing unit (CPU) 410, a memory 414, a digital signal processor (DSP) 418, a disk 420, and a removable media 424. The CPU 410 may be a conventional complex instruction set computer (CISC) or a reduced instruction set computer

10

15

20

(RISC). The memory 414 may be homogeneous or a mixture of kinds of memory, and may include dynamic random-access memory (DRAM), static random-access memory (SRAM), flash-programmable read-only memory (Flash), or other kinds of read-only memory (ROM). An optional DSP 418 may be included to facilitate complex numerical calculations. Disk 420 may be magnetic, optical, or magneto-optical in nature. In other embodiments, a large area of non-volatile memory may be used instead of a disk 420 for program storage. Removable media 424 may be a removable magnetic disk, a floppy disk, an optical disk, a magneto-optical disk, or a memory card.

The components of the computer 310 may be connected by a central data bus 404. Additionally, local busses may be used, such as local bus 412 between CPU 410 and memory 414, or local bus 416 between DSP 418 and memory 414. Various input/output (I/O) controllers such as universal serial bus (USB) couplers 428, 438, local area network (LAN) coupler 430, and graphics engine 434 may also be connected via data bus 404. In alternate embodiments other interfaces may be used to connect with the scanner 314, the laser printer 318, the monitor 322, and the keyboard 326.

Referring now to Figure 5, a software module diagram of one embodiment of the computer system is disclosed, in accordance with the present invention. In the Figure 5 embodiment, the computer 310

10

15

20

controls the scanning performed by the scanner 314. Computer 310 also performs the screen conversion filter process and the line smoothing filter process. Software modules scanning driver 510, first convolution filter 520, and second convolution filter 530 may be resident within memory 414. In other embodiments, these three processes may be performed by a smart scanner, a smart laser printer, or by a digital photocopier.

First convolution filter 520 may serve as the screen conversion filter. In alternate embodiments, first convolution filter 520 may serve as the line smoothing filter. Second convolution filter 530 may serve as the line smoothing filter. In alternate embodiments, second convolution filter 530 may serve as the screen conversion filter. Details of these filters will be provided in connection with Figures 6, 7A, and 7B below.

Referring now to Figure 6, a chart illustrating the calculation of a filtered value for a pixel is shown, according to one embodiment of the present invention. Matrix 600 represents the digital representation of the scanned halftone print. Each location within the matrix 600 is a picture element (pixel) and contains a numeric value (for monochrome scanners) or a set of three numeric values (for color scanners) representing the brightness of the pixel. In the following discussion it will be assumed that the single numeric value (monochrome) example will be discussed, but it should be noted that the three numeric value

10

15

20

(color) embodiment merely replicates the monochrome filtering process three times.

An exemplary pixel is pixel 620, in the i'th column and j'th row of matrix 600. Pixel 620 will be used to show the operation of one of the convolution filters. Let the original numeric value in pixel 620 be a_{ij} . The filtered value for the pixel 620 may be called b_{ij} . The value of b_{ij} is derived by taking a linear combination of a_{ij} and the values of the 8 neighboring pixels 612, 614, 616, 618, 622, 624, and 628 in a 3 by 3 submatrix 610 of matrix 600. In other embodiments, submatrix 610 may be a 4 by 4 submatrix, a 5 by 5 submatrix, or any other size submatrix. The matrix of all the b_{ij} (not shown) is the output matrix of the convolution filter.

Referring now to Figure 7A, a diagram of a first convolution filter is shown, according to one embodiment of the present invention. In this embodiment, the filter of Figure 7A forms a screen conversion filter. In alternate embodiments, the filter of Figure 7A may be used as a line smoothing filter. Coefficient matrix 700 contains the constant coefficients which will be used in the first convolution filter. The elements of coefficient matrix 700 are zero everywhere except on the diagonal going from upper left to lower right. Here c(+1, -1) = c(-1, +1) = 1, and c(0, 0) = 2. The coefficients are multiplied by the corresponding pixel's numeric values in each submatrix. All these products are then

10

15

20

summed to give the output numeric value b_{ij} . The double summation in the equation of Figure 7A collapses to a simple sum, since $2a_{ij} = a_{ij} + a_{ij}$. Therefore the first convolution filter of Figure 7A may be calculated in an efficient manner with three additions and no multiplications.

Referring now to Figure 7B, a diagram of a second convolution filter is shown, according to one embodiment of the present invention. In this embodiment, the filter of Figure 7B forms a line smoothing filter. In alternate embodiments, the filters of Figure 7A and 7B may be reversed, with the filter of Figure 7B being used as the screen conversion filter. Coefficient matrix 750 contains the constant coefficients which will be used in the second convolution filter. The elements of coefficient matrix 750 are zero everywhere except on the diagonal going from lower left to upper right. Here $c_{(+1,+1)} = c_{(-1,-1)} = 1$, and $c_{(0,0)} = 2$. As in the case of the first convolution filter of Figure 7A, the coefficients are multiplied by the corresponding pixel's numeric values in each submatrix. All these products are then summed to give the output numeric value b_{ii}. The double summation in the equation of Figure 7B again collapses to a simple sum, since $2a_{ij} = a_{ij} + a_{ij}$. Therefore the second convolution filter of Figure 7B may also be calculated in an efficient manner with three additions and no multiplications.

Referring now to Figure 8, a diagram of a scanned image of one embodiment of the present invention is shown. In the Figure 8

10

15

20

example, a CMYK halftone print has been created using a method similar to that outlined in the discussions of Figure 1 and Figure 2 above. The round "rosette" marks are common to halftone prints when examined at great magnification. The halftone print has been digitally scanned and the resulting data placed into a pixel matrix similar to that shown in Figure 6 above. What is shown in Figure 8 is the resulting image if this pixel matrix were printed directly onto a high-resolution laser printer.

Referring now to Figure 9, a diagram of an output image from a first convolution filter is shown, according to one embodiment of the present invention. In the Figure 9 example, the data representing the image of Figure 8 was processed in a first convolution filter, such as that shown in Figure 7A, used as a screen conversion filter. The Figure 7A filter, when used in this manner, produces lines along a 45 degree angle. It should be noted that the Figure 9 image is for illustration only as this is an intermediary result. In other embodiments, using the Figure 7B filter as a screen conversion filter may produce lines along a 135 degree angle.

It is noteworthy that the filtering as shown in the Figure 9 example does not produce Moire patterns. The resulting lines along the 45 degree angle (or 135 degree angle) are parallel and thus have an angle of 0 degrees between them. It is well-known in the art that

10

15

20

patterns of intersecting lines intersecting at an angle of θ may produce Moire patterns with a interference period T given by $T = K/\sin(\theta/2)$, where K is a constant of proportion. Since in the present example $\theta = 0$, and since $\sin(0) = 0$, the interference period T is infinite. Hence the use of the Figure 7A filter to produce the exemplary image of Figure 9 has the benefit of preventing Moire effects.

Referring now to Figure 10, a diagram of an output image from a second filter is shown, according to one embodiment of the present invention. This image presumes that the Figure 9 filtering was first performed with the filter of Figure 7A. The Figure 10 filtering, the line smoothing filtering step, would then be accomplished with the filter of Figure 7B. In an alternate embodiment, the Figure 7B filter would be used as the screen conversion filter followed by the Figure 7A filter as the line smoothing filter.

The image shown in Figure 10 is an exemplary final result of the filtering process of the present invention. From the point of view of a subsequent laser printer or photocopier, this image loses most of the artifacts originally introduced by the halftone process. In effect, the artifacts introduce by the halftone screens have been removed, which leads to the filtering process of the present invention being referred to as a "de-screening filter". In no part of the de-screening process were the original parameters of the halftone process required. The de-

10

15

20

screening process of the present invention works independently of any previous halftone screening processes.

Referring now to Figure 11, a graph of a first filter frequency response is shown, according to one embodiment of the present invention. This graph illustrates the frequency response of the filter of Figure 7A. If the input values a_{ij} at each location of a matrix are considered as a function of a two dimensional discrete-valued variable, then the frequency response of the filter of Figure 7A may be derived using techniques well-known in the art. The frequency response curve shown in Figure 11 has the result of passing low-frequencies, passing high-frequencies along the diagonal line from lower left to upper right, and attenuating high-frequencies away from this diagonal line (e.g. along the horizontal and vertical axis). Alternate filters to that of Figure 7A may be used when the alternate filter has a frequency response curve similar to that shown in Figure 11.

Referring now to Figure 12, a graph of a second filter frequency response is shown, according to one embodiment of the present invention. This graph illustrates the frequency response of the filter of Figure 7B. The frequency response curve shown in Figure 12 has the result of passing low-frequencies, passing high-frequencies along the diagonal line from lower right to upper left, and attenuating high-frequencies away from this diagonal line (e.g. along the horizontal and

10

15

20

vertical axis). Alternate filters to that of Figure 7B may be used when the alternate filter has a frequency response curve similar to that shown in Figure 12.

Referring now to Figure 13, a graph of a combined filter frequency response is shown, according to another embodiment of the present invention. In this alternate embodiment, instead of the two cascaded filters of Figure 7A and Figure 7B, a single convolution filter may be utilized. The single convolution filter of the Figure 13 embodiment may have a frequency response as given in Figure 13 or a frequency response similar to that given in Figure 13. The derivation of filter coefficients for use in a coefficient matrix, similar to coefficient matrices 700, 750, from a given frequency response graph is well-known in the art.

In the foregoing specification, the invention has been described with reference to specific exemplary embodiments thereof. It will, however, be evident that various modifications and changes may be made thereto without departing from the broader spirit and scope of the invention as set forth in the appended claims. The specification and drawings are, accordingly, to be regarded in an illustrative rather than a restrictive sense.

CLAIMS

What is claimed is:

performing a screen conversion filter upon a scanned representation of said halftone image to produce an intermediate image; and performing a line smoothing filter upon said intermediate image to produce an output image.	1	1. A method for de-screening a halftone image, comprising:
intermediate image; and performing a line smoothing filter upon said intermediate image	2	performing a screen conversion filter upon a scanned
5 performing a line smoothing filter upon said intermediate imag	3	representation of said halftone image to produce an
	4	intermediate image; and
6 to produce an output image.	5	performing a line smoothing filter upon said intermediate image
	6	to produce an output image.

- 1 2. The method of claim 1, wherein said screen conversion 2 filter utilizes a 3 by 3 coefficient matrix.
- 3. The method of claim 2, wherein said coefficient matrix is
 diagonal along the lower right to upper left direction.
- 1 4. The method of claim 3, wherein coefficients $c_{(-1,\ 1)}=c_{(1,\ -1)}=$ 2 1, and coefficient $c_{(0,\ 0)}=2$.
- 1 5. The method of claim 2, wherein said coefficient matrix is 2 diagonal along the lower left to upper right direction.

- 1 6. The method of claim 3, wherein coefficients $c_{(-1,-1)} = c_{(1,1)} =$
- 2 1, and coefficient $c_{(0,0)} = 2$.
- The method of claim 1, wherein said line smoothing filter
- 2 utilizes a 3 by 3 coefficient matrix.
- 1 8. The method of claim 7, wherein said coefficient matrix is
- 2 diagonal along the lower right to upper left direction.
- 1 9. The method of claim 8, wherein coefficients $c_{(-1, 1)} = c_{(1, -1)} =$
- 2 1, and coefficient $c_{(0,0)} = 2$.
- 1 10. The method of claim 9, wherein said coefficient matrix is
- 2 diagonal along the lower left to upper right direction.
- 1 11. The method of claim 10, wherein coefficients $c_{(-1,-1)} = c_{(1,1)} =$
- 2 1, and coefficient $c_{(0,0)} = 2$.
- 1 12. The method of claim 1, wherein said screen conversion
- 2 filter passes low-frequencies, passes high-frequencies along a diagonal
- 3 line from lower left to upper right, and attenuates high-frequencies
- 4 away from said diagonal line.

2

3

4

5

6

1	13. The method of claim 1, wherein said screen conversion
2	filter passes low-frequencies, passes high-frequencies along a diagonal
3	line from lower right to upper left, and attenuates high-frequencies
4	away from said diagonal line.

- 1 14. The method of claim 1, wherein said line smoothing filter
 2 passes low-frequencies, passes high-frequencies along a diagonal line
 3 from lower left to upper right, and attenuates high-frequencies away
 4 from said diagonal line.
- 1 15. The method of claim 1, wherein said line smoothing filter
 2 passes low-frequencies, passes high-frequencies along a diagonal line
 3 from lower right to upper left, and attenuates high-frequencies away
 4 from said diagonal line.
 - 16. A method for de-screening a halftone image, comprising:

 performing a single convolution filter upon a scanned

 representation of said halftone image to produce an

 output image, wherein said single convolution filter equals

 the resulting convolution of a screen conversion filter and a

 line smoothing filter.

image; and

1	17. The method of claim 16, wherein said single convolution
2	filter passes low-frequencies, passes high-frequencies at a central area
3	and attenuates high-frequencies along a horizontal axis and a vertical
4	axis.

- 1 18. A computer-readable medium having stored thereon
 2 sequences of instructions, the sequences of instructions including
 3 instructions which, when executed by a processor, causes the processor
 4 to perform various processing, the sequences of instructions
 5 comprising:
 6 a first sequence to perform a screen conversion filter upon a
 7 scanned representation of a halftone image to produce an intermediate
- 9 a second sequence to perform a line smoothing filter upon said 10 intermediate image to produce an output image.
- 1 19. A computer-readable medium having stored thereon 2 sequences of instructions, the sequences of instructions including 3 instructions which, when executed by a processor, causes the processor 4 to perform various processing, the sequences of instructions 5 comprising:

2

3

4

5

6

1

2

3

4

5

6	a first sequence to perform a single convolution filter upon a
7	scanned representation of a halftone image to produce an output image,
8	wherein said single convolution filter equals the resulting convolution of
9	a screen conversion filter and a line smoothing filter.

- 20. A system for de-screening a halftone image, comprising:

 a memory to store an input image from a halftone print; and
 a processor to perform a screen conversion filter upon said input
 image and create an intermediate image, and to perform a
 line smoothing filter upon said intermediate image and
 create an output image.
- 21. A method for de-screening a halftone image, comprising: converting dots of said halftone image into parallel lines of an intermediate image; and smoothing said parallel lines of said intermediate image into a final image.
- 1 22. The method of claim 21, wherein said parallel lines are at 2 an approximately 45 degree angle with respect to a side of said 3 intermediate image.

10

ABSTRACT OF THE DISCLOSURE

A method and apparatus for de-screening a halftone image, therefore allowing the recovery of an approximation of an original image, is disclosed. A method according to one embodiment first performs a screen conversion filter upon a scanned representation of the halftone image to produce an intermediate image. This method then performs a line smoothing filter upon the intermediate image to produce an approximation to the original image.

In an alternate embodiment, the method performs a single convolution filter upon a scanned representation of the halftone image to produce an approximation to the original image. In this embodiment, the single convolution filter is equal to the resulting convolution of first performing a screen conversion filter and then performing a line smoothing filter.






FIGURE 1



Traditional Screen Angles







FIGURE 4



Flaure 5

22-141 50 SHEETS 22-142 100 SHEETS 22-144 200 SHEETS

009~			610 ~ 612 614 616 j+1	ç 719 013 819	1-1 624 626 628 3-1	2-1 1 1.41	
		1 1			1		
					i		
					1		
					1		
			~02g				
			9				
			4				

FIGURE 6

50 SHEETS 100 SHEETS 200 SHEETS 22-141 22-142 22-144

00/~

 $C_{-1,1} = C_{1,-1} = 1$

. All other CKB = 0 Co,0 = 2

 $b_{ij} = \sum_{k=-1}^{1} \sum_{k=-1}^{2} a_{ik,k}(j,t) C_{kl} =$

= d(1-1)(j+1) + d(1+1)(j-1) + 2 dij

FIGURE 7A

Ckl

C0,0 = 2 000

All other Ckg = 0 $C_{-1,-1} = C_{1,1} = 1$

= d(i+1)(f+1)+ a(1-1)f-1)+2 aig

FIGURE 7B

Cke

IMAGE SCANNED USING THE ASTRA 2400S




FIGURE 8

OUTPUT OF FIRST CONVOLUTION FILTER




Figure 9

OUTPUT OF SECOND CONVOLUTION FILTER




FIGURE 10

SCREEN CONVERSION FILTER FREQUENCY RESPONSE




FIGURE 11

LINE SMOOTHING FILTER FREQUENCY RESPONSE




FIGURE 12

DESCRIPTION FILTER FREQUENCY RESPONSE




FIGURE 13

Attorney's Docket No.: <u>03551.P007</u> Patent

DECLARATION AND POWER OF ATTORNEY FOR PATENT APPLICATION

As a below named inventor, I hereby declare that:

the specification of which

My residence, post office address and citizenship are as stated below, next to my name.

I believe I am the original, first, and sole inventor (if only one name is listed below) or an original, first, and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled

SYSTEM AND METHOD FOR A ROBUST DE-SCREENING FILTER

as
ıble)
2

I hereby state that I have reviewed and understand the contents of the above-identified specification, including the claim(s), as amended by any amendment referred to above. I do not know and do not believe that the claimed invention was ever known or used in the United States of America before my invention thereof, or patented or described in any printed publication in any country before my invention thereof or more than one year prior to this application, that the same was not in public use or on sale in the United States of America more than one year prior to this application, and that the invention has not been patented or made the subject of an inventor's certificate issued before the date of this application in any country foreign to the United States of America on an application filed by me or my legal representatives or assigns more than twelve months (for a utility patent application) or six months (for a design patent application) prior to this application.

I acknowledge the duty to disclose all information known to me to be material to patentability as defined in Title 37, Code of Federal Regulations, Section 1.56.

I hereby claim foreign priority benefits under Title 35, United States Code, Section 119(a)-(d), of any foreign application(s) for patent or inventor's certificate listed below and have also identified below any foreign application for patent or inventor's certificate having a filing date before that of the application on which priority is claimed:

Prior Foreign Application(s)							
(Number)	(Country)	(Day/Month/Year Filed)	Yes	No			
(Number)	(Country)	(Day/Month/Year Filed)	Yes	No			
(Number)	(Country)	(Day/Month/Year Filed)	Yes	No			

Priority

I hereby claim the benefit under to provisional application(s) listed b		de, Section 119(e) of any United States
(Application Number)	Filing Date	
(Application Number)	Filing Date	-
application(s) listed below and, ir is not disclosed in the prior Unite of Title 35, United States Code, S known to me to be material to pa	nsofar as the subject mand States application in the Section 112, I acknowled tentability as defined in Itable between the filing of	ode, Section 120 of any United States tter of each of the claims of this application he manner provided by the first paragraph lige the duty to disclose all information Fitle 37, Code of Federal Regulations, late of the prior application and the national
(Application Number)	Filing Date	(Status patented, pending, abandoned)
(Application Number)	Filing Date	(Status patented, pending, abandoned)
part of this document) as my res	pective patent attorneys osecute this application	(which is incorporated by reference and a and patent agents, with full power of and to transact all business in the Patent
Send correspondence to <u>Dennis A. Nicholls</u> , BLAKELY, SOKOLOFF, TAYLOR & (Name of Attorney or Agent) ZAFMAN LLP, 12400 Wilshire Boulevard 7th Floor, Los Angeles, California 90025 and direct telephone calls to <u>Dennis A. Nicholls</u> , (408) 720-8300. (Name of Attorney or Agent)		
I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.		
Full Name of Sole/First Inventor		
Inventor's Signature	o u du	Date 8/3/2000
Residence Ayer, Massachusetts	State)	Date
Post Office Address 44 Mulberry Circle Ayer, Massachusetts 01432 USA		

APPENDIX A

William E. Alford, Reg. No. 37,764; Farzad E. Amini, Reg. No. P42,261; Aloysius T. C. AuYeung, Reg. No. 35,432; William Thomas Babbitt, Reg. No. 39,591; Carol F. Barry, Reg. No. 41,600; Jordan Michael Becker, Reg. No. 39,602; Bradley J. Bereznak, Reg. No. 33,474; Michael A. Bernadicou, Reg. No. 35,934; Roger W. Blakely, Jr., Reg. No. 25,831; Gregory D. Caldwell, Reg. No. 39,926; Ronald C. Card, Reg. No. 44,587; Andrew C. Chen, Reg. No. 43,544; Thomas M. Coester, Reg. No. 39,637; Alin Corie, Reg. No. P46.244: Dennis M. deGuzman, Reg. No. 41,702; Stephen M. De Klerk, under 37 C.F.R. § 10.9(b); Michael Anthony DeSanctis, Reg. No. 39,957; Daniel M. De Vos, Reg. No. 37,813; Robert Andrew Diehl, Reg. No. 40,992; Sanjeet Dutta, Reg. No. P46,145; Matthew C. Fagan, Reg. No. 37,542; Tarek N. Fahmi, Reg. No. 41,402; Paramita Ghosh, Reg. No. 42,806; James Y. Go, Reg. No. 40,621; James A. Henry, Reg. No. 41,064; Willmore F. Holbrow III, Reg. No. P41,845; Sheryl Sue Holloway, Reg. No. 37,850; George W Hoover II, Reg. No. 32,992; Eric S. Hyman, Reg. No. 30,139; William W. Kidd, Reg. No. 31,772; Sang Hui Kim, Reg. No. 40,450; Eric T. King, Reg. No. 44,188; Erica W. Kuo, Reg. No. 42,775; Kurt P. Leyendecker, Reg. No. 42,799; Michael J. Mallie, Reg. No. 36,591; Andre L. Marais, under 37 C.F.R. § 10.9(b); Paul A. Mendonsa, Reg. No. 42,879; Darren J. Milliken, Reg. 42,004; Lisa A. Norris, Reg. No. 44,976; Chun M. Ng, Reg. No. 36,878; Thien T. Nguyen, Reg. No. 43,835; Thinh V. Nguyen, Reg. No. 42,034; Dennis A. Nicholls, Reg. No. 42,036; Daniel E. Ovanezian, Reg. No. 41,236; Marina Portnova, Reg. No. P45,750; Babak Redjaian, Reg. No. 42,096; William F. Ryann, Reg. 44,313; James H. Salter, Reg. No. 35,668; William W. Schaal, Reg. No. 39,018; James C. Scheller, Reg. No. 31,195; Jeffrey Sam Smith, Reg. No. 39,377; Maria McCormack Sobrino, Reg. No. 31,639; Stanley W. Sokoloff, Reg. No. 25,128; Judith A. Szepesi, Reg. No. 39,393; Vincent P. Tassinari, Reg. No. 42,179; Edwin H. Taylor, Reg. No. 25,129; John F. Travis, Reg. No. 43,203; George G. C. Tseng, Reg. No. 41,355; Joseph A. Twarowski, Reg. No. 42,191; Lester J. Vincent, Reg. No. 31,460; Glenn E. Von Tersch, Reg. No. 41,364; John Patrick Ward, Reg. No. 40,216; Mark L. Watson, Reg. No. P46,322; Thomas C. Webster, Reg. No. P46,154; Charles T. J. Weigell, Reg. No. 43,398; Kirk D. Williams, Reg. No. 42,229; James M. Wu, Reg. No. 45,241; Steven D. Yates, Reg. No. 42,242; and Norman Zafman, Reg. No. 26,250; my patent attorneys, and Justin M. Dillon, Reg. No. 42,486; my patent agent, of BLAKELY, SOKOLOFF, TAYLOR & ZAFMAN LLP, with offices located at 12400 Wilshire Boulevard, 7th Floor, Los Angeles, California 90025, telephone (310) 207-3800, and James R. Thein, Reg. No. 31,710, my patent attorney.

APPENDIX B

Title 37, Code of Federal Regulations, Section 1.56

<u>Duty to Disclose Information Material to Patentability</u>

- (a) A patent by its very nature is affected with a public interest. The public interest is best served, and the most effective patent examination occurs when, at the time an application is being examined, the Office is aware of and evaluates the teachings of all information material to patentability. Each individual associated with the filing and prosecution of a patent application has a duty of candor and good faith in dealing with the Office, which includes a duty to disclose to the Office all information known to that individual to be material to patentability as defined in this section. The duty to disclosure information exists with respect to each pending claim until the claim is cancelled or withdrawn from consideration, or the application becomes abandoned. Information material to the patentability of a claim that is cancelled or withdrawn from consideration need not be submitted if the information is not material to the patentability of any claim remaining under consideration in the application. There is no duty to submit information which is not material to the patentability of any existing claim. The duty to disclosure all information known to be material to patentability is deemed to be satisfied if all information known to be material to patentability of any claim issued in a patent was cited by the Office or submitted to the Office in the manner prescribed by §§1.97(b)-(d) and 1.98. However, no patent will be granted on an application in connection with which fraud on the Office was practiced or attempted or the duty of disclosure was violated through bad faith or intentional misconduct. The Office encourages applicants to carefully examine:
 - (1) Prior art cited in search reports of a foreign patent office in a counterpart application, and
- (2) The closest information over which individuals associated with the filing or prosecution of a patent application believe any pending claim patentably defines, to make sure that any material information contained therein is disclosed to the Office.
- (b) Under this section, information is material to patentability when it is not cumulative to information already of record or being made or record in the application, and
- (1) It establishes, by itself or in combination with other information, a prima facie case of unpatentability of a claim; or
 - (2) It refutes, or is inconsistent with, a position the applicant takes in:
 - (i) Opposing an argument of unpatentability relied on by the Office, or
 - (ii) Asserting an argument of patentability.

A prima facie case of unpatentability is established when the information compels a conclusion that a claim is unpatentable under the preponderance of evidence, burden-of-proof standard, giving each term in the claim its broadest reasonable construction consistent with the specification, and before any consideration is given to evidence which may be submitted in an attempt to establish a contrary conclusion of patentability.

- (c) Individuals associated with the filing or prosecution of a patent application within the meaning of this section are:
 - (1) Each inventor named in the application;
 - (2) Each attorney or agent who prepares or prosecutes the application; and
- (3) Every other person who is substantively involved in the preparation or prosecution of the application and who is associated with the inventor, with the assignee or with anyone to whom there is an obligation to assign the application.
- (d) Individuals other than the attorney, agent or inventor may comply with this section by disclosing information to the attorney, agent, or inventor.